山东·济宁



BACKHOE LOADER SERIES
挖掘装载机系列

HW08-12 BACKHOE LOADER

HW08-12 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW08-12 excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数
Machine detailed parameters

HW08-12 技术参数			
外形尺寸 Dimensions	5100*1350*2580mm	正铲动作时间和 Front shovel action time and	12s
轴距 Wheelbase	1960mm	发动机型号 Engine model	常柴 390（可选云内 490）
轮距 Track width	1130mm	发动机型式 Engine type	三冲程（四冲程） Three-stroke (four-stroke)
最小离地间隙 Minimum ground clearance	250mm	额定功率 Rated power	25（37）KW
系统压力 System pressure	16MPa	额定转速 Rated speed	2400 r/min
整机重量 Machine weight	2870kg	气缸数 - 内径 Number of cylinders - inner diameter	3-90（4-90）
最高车速 Maximum speed	20km/h	变速箱 Gearbox	定轴式动力换挡 Fixed shaft power shift
最大爬坡能力 Maximum gradeability	25°	档位数 Number of stalls	前 2 后 2Front 2 Back 2
最小转弯半径 Minimum turning radius	3200mm	液力变矩器 Torque Converter	ZL28F
最大挖掘深度 Maximum digging depth	1500mm	转向方式 Steering method	铰接全液压转向 Articulated full hydraulic steering
挖掘卸载高度 Excavation unloading height	1800mm	转向角度 Steering angle	33°
最大挖掘半径 Maximum digging radius	2600mm	型式 Type	130
挖斗宽度 Bucket width	350mm	轮胎规格 Tire specifications	825-16
挖斗斗容 Bucket capacity	0.08m³	前轮气压 Front wheel air pressure	250 KPa
挖掘最大高度 Maximum digging height	2300mm	后轮气压 Rear wheel air pressure	250 KPa
最大挖掘力 Maximum digging force	25KN	行车制动 Service brake	油刹鼓式制动 Oil brake drum brake
挖机回转角度 Excavator rotation angle	180°	驻车制动 Parking brake	手动 Manual
最大卸载高度 Unloading height	2300mm	燃油箱 Fuel tank	20 L
最大卸载距离 Maximum unloading distance	800mm	液压油箱 Hydraulic tank	20 L
装斗斗容 Bucket capacity	0.4m³	驱动型式 Drive type	四轮驱动 Four-wheel drive
装载最大举升高度 Loading Max. Lifting Height	3000mm	变速型式 Gear type	液力变速 Hydraulic transmission
最大崛起力 Maximum rise	28KN	刹车距离 Braking distance	300mm

HW10-20 BACKHOE LOADER

HW10-20 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW10-20 excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数
Machine detailed parameters

HW10-20 技术参数			
外形尺寸 Dimensions	5500*1750*2650mm	正铲动作时间和 Front shovel action time and	12s
轴距 Wheelbase	2070mm	发动机型号 Engine model	云内 YN25GB
轮距 Track width	1475mm	发动机型式 Engine type	直喷四冲程 Direct Injection Four-Stroke
最小离地间隙 Minimum ground clearance	250mm	额定功率 Rated power	37kw
系统压力 System pressure	16MPa	额定转速 Rated speed	2400r/min
整机重量 Machine weight	3400kg	气缸数 - 内径 Number of cylinders - inner diameter	4-90
最高车速 Maximum speed	25km/h	变速箱 Gearbox	定轴式动力换挡 fixed shaft power shift
最大爬坡能力 Maximum gradeability	25°	档位数 Number of stalls	前 2 后 2Front 2 Back 2
最小转弯半径 Minimum turning radius	3500mm	液力变矩器 Torque Converter	ZL28F
最大挖掘深度 Maximum digging depth	2000mm	转向方式 Steering method	铰接全液压转向 Articulated full hydraulic steering
挖掘卸载高度 Excavation unloading height	1800mm	转向角度 Steering angle	33°
最大挖掘半径 Maximum digging radius	2700mm	轮胎规格 Tire specifications	20.5-16
挖斗宽度 Bucket width	400mm	前轮气压 Front wheel air pressure	250KPa
挖斗斗容 Bucket capacity	0.1m³	后轮气压 Rear wheel air pressure	250KPa
挖掘最大高度 Maximum digging height	3300mm	行车制动 Service brake	油刹鼓式制动 Oil brake drum brake
最大挖掘力 Maximum digging force	25KN	驻车制动 Parking brake	手动 Manually
挖机回转角度 Excavator rotation angle	180°	燃油箱 Fuel tank	30L
最大卸载高度 Unloading height	2800mm	液压油箱 Hydraulic tank	30L
最大卸载距离 Maximum unloading distance	800mm	驱动型式 Drive type	四轮驱动 Four-wheel drive
装斗斗容 Bucket capacity	0.5m³	变速型式 Gear type	液力变速 Hydraulic transmission
装载最大举升高度 Loading Max. Lifting Height	3300mm	刹车距离 Braking distance	330mm
最大崛起力 Maximum rise	36KN		

HW15-26 BACKHOE LOADER

HW15-26 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW15-26 excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数
Machine detailed parameters

HW15-26 技术参数			
外形尺寸 Dimensions	5800*1850*2750mm	正铲动作时间和 Front shovel action time and	12s
轴距 Wheelbase	2315mm	发动机型号 Engine model	云内 Yunnei YN27GBZ
轮距 Track width	1500mm	发动机型式 Engine type	涡轮增压四冲程 Turbocharged four-stroke
最小离地间隙 Minimum ground clearance	220mm	额定功率 Rated power	58
系统压力 System pressure	16MPa	额定转速 Rated speed	2400r/min
整机重量 Machine weight	4600kg	气缸数 - 内径 Number of cylinders - inner diameter	4-90
最高车速 Maximum speed	26km/h	变速箱 Gearbox	定轴式动力换挡 fixed shaft power shift
最大爬坡能力 Maximum gradeability	25°	档位数 Number of stalls	前 2 后 2Front 2 Back 2
最小转弯半径 Minimum turning radius	4000mm	液力变矩器 Torque Converter	ZL29A
最大挖掘深度 Maximum digging depth	2700mm	转向方式 Steering method	铰接全液压转向 Articulated full hydraulic steering
挖掘卸载高度 Excavation unloading height	2200mm	转向角度 Steering angle	33°
最大挖掘半径 Maximum digging radius	4600mm	型式 Type	轮边 Wheel side
挖斗宽度 Bucket width	600mm	轮胎规格 Tire specifications	23.5-16
挖斗斗容 Bucket capacity	0.2m³	前轮气压 Front wheel air pressure	250KPa
挖掘最大高度 Maximum digging height	4200mm	后轮气压 Rear wheel air pressure	250KPa
最大挖掘力 Maximum digging force	28KN	行车制动 Service brake	气顶油钳盘制动 Air over oil caliper brake
挖机回转角度 Excavator rotation angle	180°	驻车制动 Parking brake	手动 Manually
最大卸载高度 Unloading height	3300mm	燃油箱 Fuel tank	40L
最大卸载距离 Maximum unloading distance	850mm	液压油箱 Hydraulic tank	40L
装斗斗容 Bucket capacity	0.7m³	驱动型式 Drive type	四轮驱动 Four-wheel drive
装载最大举升高度 Loading Max. Lifting Height	4200mm	变速型式 Gear type	液力变速 Hydraulic transmission
最大崛起力 Maximum rise	36KN	刹车距离 Braking distance	450mm

HW20-28 BACKHOE LOADER

HW20-28 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW20-28 excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数
Machine detailed parameters

HW20-28 技术参数			
外形尺寸 Dimensions	6200*1960*2800mm	正铲动作时间和 Front shovel action time and	12s
轴距 Wheelbase	2550mm	发动机型号 Engine model	云内 Yunnei YN27GBZ
轮距 Track width	1580mm	发动机型式 Engine type	涡轮增压四冲程 Turbocharged four-stroke
最小离地间隙 Minimum ground clearance	290mm	额定功率 Rated power	76
系统压力 System pressure	18MPa	额定转速 Rated speed	2400r/min
整机重量 Machine weight	5400kg	气缸数 - 内径 Number of cylinders - inner diameter	4-102
最高车速 Maximum speed	28km/h	变速箱 Gearbox	定轴式动力换挡 fixed shaft power shift
最大爬坡能力 Maximum gradeability	25°	档位数 Number of stalls	前 2 后 2Front 2 Back 2
最小转弯半径 Minimum turning radius	4500mm	液力变矩器 Torque Converter	ZL29A
最大挖掘深度 Maximum digging depth	2600mm	转向方式 Steering method	铰接全液压转向 Articulated full hydraulic steering
挖掘卸载高度 Excavation unloading height	2300mm	转向角度 Steering angle	33°
最大挖掘半径 Maximum digging radius	4600mm	型式 Type	轮边 Wheel side
挖斗宽度 Bucket width	600mm	轮胎规格 Tire specifications	16/70-20
挖斗斗容 Bucket capacity	0.2m³	前轮气压 Front wheel air pressure	250KPa
挖掘最大高度 Maximum digging height	4300mm	后轮气压 Rear wheel air pressure	250KPa
最大挖掘力 Maximum digging force	28KN	行车制动 Service brake	气顶油钳盘制动 Air over oil caliper brake
挖机回转角度 Excavator rotation angle	180°	驻车制动 Parking brake	手动 Manually
最大卸载高度 Unloading height	3500mm	燃油箱 Fuel tank	50L
最大卸载距离 Maximum unloading distance	900mm	液压油箱 Hydraulic tank	50L
装斗斗容 Bucket capacity	1m³	驱动型式 Drive type	四轮驱动 Four-wheel drive
装载最大举升高度 Loading Max. Lifting Height	4300mm	变速型式 Gear type	液力变速 Hydraulic transmission
最大崛起力 Maximum rise	42KN	刹车距离 Braking distance	600mm

HW25-30 BACKHOE LOADER

HW25-30 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW25-30 excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数
Machine detailed parameters

HW25-30 技术参数			
外形尺寸 Dimensions	6500*2040*2800mm	正铲动作时间和 Front shovel action time and	12s
轴距 Wheelbase	2675mm	发动机型号 Engine model	云内 Yunnei YN48GBZ
轮距 Track width	1630mm	发动机型式 Engine type	涡轮增压四冲程 Turbocharged four-stroke
最小离地间隙 Minimum ground clearance	280mm	额定功率 Rated power	92
系统压力 System pressure	18MPa	额定转速 Rated speed	2400r/min
整机重量 Machine weight	6000kg	气缸数 - 内径 Number of cylinders - inner diameter	4-108
最高车速 Maximum speed	28km/h	变速箱 Gearbox	定轴式动力换挡 fixed shaft power shift
最大爬坡能力 Maximum gradeability	25°	档位数 Number of stalls	前 2 后 2Front 2 Back 2
最小转弯半径 Minimum turning radius	4500mm	液力变矩器 Torque Converter	ZL29A
最大挖掘深度 Maximum digging depth	2600mm	转向方式 Steering method	铰接全液压转向 Articulated full hydraulic steering
挖掘卸载高度 Excavation unloading height	2300mm	转向角度 Steering angle	33°
最大挖掘半径 Maximum digging radius	4600mm	型式 Type	轮边 Wheel side
挖斗宽度 Bucket width	600mm	轮胎规格 Tire specifications	16/70-20
挖斗斗容 Bucket capacity	0.25m³	前轮气压 Front wheel air pressure	250KPa
挖掘最大高度 Maximum digging height	4300mm	后轮气压 Rear wheel air pressure	250KPa
最大挖掘力 Maximum digging force	28KN	行车制动 Service brake	气顶油钳盘制动 Air over oil caliper brake
挖机回转角度 Excavator rotation angle	180°	驻车制动 Parking brake	手动 Manually
最大卸载高度 Unloading height	3500mm	燃油箱 Fuel tank	50L
最大卸载距离 Maximum unloading distance	900mm	液压油箱 Hydraulic tank	50L
装斗斗容 Bucket capacity	1.2m³	驱动型式 Drive type	四轮驱动 Four-wheel drive
装载最大举升高度 Loading Max. Lifting Height	4300mm	变速型式 Gear type	液力变速 Hydraulic transmission
最大崛起力 Maximum rise	42KN	刹车距离 Braking distance	620mm

HW40-28(T) BACKHOE LOADER

HW40-28(T) 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW40-28 (T) excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数
Machine detailed parameters

HW40-28(T) 技术参数			
整机操作重量 Overall Operating Weight	7800kg	**驱动桥 Axle**	
运输尺寸 Transport Dimension		主传动类型 Main Transmission Type	双减速 Double Reduction
长 × 宽 × 高 L*W*H	7600×2260×2890mm	轮边减速型式 Final Reducer	一级轮边减速 Single Stage Final Reducer
轴距 Wheel base	2250mm	额定载重 Rated Loader of Axle	4/18.5t
最小离地间隙 Min. Ground Clearance	300mm	**变矩器 Torque Converter**	
装载斗容 Bucket Capacity	1.5m³	型号 Model	YJ280
掘起力 Breakout Force	38KN	型式 Type	单级、单相三元件 Single-stage Three Elements
装载举升能力 Loading Lifting Capacity	2800KG	冷却方式 Cooling Method	油冷压力循环 Oil-cooling Pressure Circulation
铲斗卸载高度 Bucket Dumping Height	2800mm	**变速箱 Gearbox**	
铲斗卸载距离 Bucket Dumping Distance	1062mm	型式 Type	定轴式动力换档 Fixed Shaft Power Transmission
反铲斗容 Backhoe Capacity	0.3m³	档位数 Gears	前进 2 档，后退 2 档
最大挖掘深度 Max. Digging Depth	4100mm	最高车速 Max.Speed	30km/h
可选挖深 Optional Digging Depth	5300mm (挖臂伸缩 Digging boom telescopic)	轮胎 Tyre	14-17.5 前轮 19.5L-24 后轮
挖斗回转角 Swing Angle of backhoe	190°	**规格 Model**	
最大牵引力 Max. Pulling Force	39KN	前轮气压 Pressure of Front wheel	0.22 Mpa
发动机 Engine		后轮气压 Pressure of Back Wheel	0.22 Mpa
品牌 / 型号 Brand/Model	YUCHAI YCD4J22T-115 涡轮增压发动机 Turbo engine	行车制动 Service Brake	气顶油钳盘制动 Air Over Oil Caliper Brake
型式 Type	单列、直喷、四冲程、水冷 In Line，Direct injection，Four-Stroke，Water Cooling		外置式 External Type
额定功率 Rated Power	85kw		自调节 Self-regulation
可选发动机 Optional Engine	YCD4T33T6-115 90KW		自平衡 Self-balance
	4BT3.9-C100 74KW	驻车 / 紧急制动 Emergency Brake	操纵力实施制动 Operation Power Implementing brake
	QSB3.9-C100 75KW		手操纵力解除制动 Manual Operation Power Terminating Brake
转向系统 Steering System		**液压系统 Hydraulic System**	
转向角 Steering Angle	±36°	液压系统压力 Pressure of Hydraulic System	22Mpa
最小转弯半径 Min. turning radius	6581mm	挖斗挖掘力 Digging Power of Excavator Grab	46.5KN
系统压力 Pressure of the system	12Mpa	铲斗掘起力 Digging Power of Dipper	31KN

HW40-28(W) BACKHOE LOADER

HW40-28 (W) 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW40-28(W) excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数
Machine detailed parameters

HW40-28(W) 技术参数			
整机操作重量 Overall Operating Weight	8200kg	**驱动桥 Axle**	
运输尺寸 Transport Dimension		主传动类型 Main Transmission Type	双减速 Double Reduction
长 × 宽 × 高 L*W*H	6050×2465×3100mm	轮边减速型式 Final Reducer	一级轮边减速 Single Stage Final Reducer
轴距 Wheel base	2280mm	额定桥载荷 Rated Bridge Load	前 Front 22.5T 后 Back18.5T
最小离地间隙 Min. Ground Clearance	300mm	**变矩器 Torque Converter**	
装载斗容 Bucket Capacity	1.0m³	型号 Model	YJ290
掘起力 Breakout Force	47KN	型式 Type	单级、单相三元件 Single-stage Three Elements
装载举升能力 Loading Lifting Capacity	2500KG	冷却方式 Cooling Method	油冷压力循环 Oil-cooling Pressure Circulation
铲斗卸载高度 Bucket Dumping Height	2650mm	**变速箱 Gearbox**	
铲斗卸载距离 Bucket Dumping Distance	1025mm	型式 Type	定轴式动力换档 Fixed Shaft Power Transmission
反铲斗容 Backhoe Capacity	0.3m³	离合器操纵油压 Clutch Control Hydraulic Pressure	1373-1569kpa
最大挖掘深度 Max. Digging Depth	4085mm	档位数 Gears	Forward 2, Reverse 2
挖斗回转角 Swing Angle of backhoe	180°	最高车速 Max.Speed	24km/h
最大牵引力 Max. Pulling Force	60KN	轮胎规格 Tyre Model	14-17.5 前轮 Front Wheel 19.5L-24 后轮 Rear Wheel
发动机 Engine		前轮气压 Pressure of Front wheel	0.4 Mpa
品牌 / 型号 Brand/Model	玉柴动力 Yuchai Power	后轮气压 Pressure of Back Wheel	0.35 Mpa
型式 Type	/	行车制动 Service Brake	气顶油钳盘制动 Air Over Oil Caliper Brake
额定功率 Rated Power	77.3kw		外置式 External Type
额定转速 Rated Speed	2200r/min		自调节 Self-regulation
最低燃油率 Min. Fuel Consumption Rate			自平衡 Self-balance
最大扭矩 Maximum Torque	400N.m	驻车 / 紧急制动 Emergency Brake	操纵力实施制动 Operation Power Implementing brake
排量 Displacement	4.837L		手操纵力解除制动 Manual Operation Power Terminating Brake
转向系统 Steering System		**液压系统 Hydraulic System**	
转向器型号 Steering Gear Model	BZZ5-250	挖斗挖掘力 Digging Power of Excavator Grab	50KN
转向角 Steering Angle	±36°	斗杆挖掘力 Bucket Cylinder Digging Force	31KN
最小转弯半径 Min. turning radius	6581mm	铲斗提升时间 Bucket Lift Time	6.8S
系统压力 Pressure of the system	12Mpa	铲斗下降时间 Bucket Lowering Time	3.1S

HW388 BACKHOE LOADER

HW388 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW388 excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数
Machine detailed parameters

HW388 技术参数			
总体尺寸 Overall dimensions		**发动机 Engine**	
外形尺寸 Overall dimensions (mm)	6150*2350*3763	型号 Model	4105 增压 Supercharging
轴距 Wheelbase (mm)	2200	型式 Type	涡轮增压 Turbocharging
轮距 Track width (mm)	1850/2000	额定功率 Rated power (kw)	85
最小离地间隙 Minimum ground clearance(mm)	300	额定转速 Rated speed (r/min)	2400
最小转弯半径 Minimum turning radius(mm)	6850	气缸数 - 内径 Number of cylinders - Inner diameter	4-105
性能参数 Performance parameters		**传动系统 Transmission system**	
系统压力 System pressure (Mpa)	28	变速箱 Gearbox	定轴式动力换挡 Fixed shaft power shift
整机重量 Complete machine weight （Kg)	7400/8400	档位数 Number of gears	前 4 后 4
最高车速 Maximum vehicle speed (km/h)	38	液力变矩器 Hydraulic torque converter	YJ280
最大爬坡能力 Maximum gradeability (°)	35	**桥 Bridge**	
挖掘参数 Excavation parameters		型式 Type	一级轮边减速桥 First-stage wheel-side reduction axle
最大伸缩挖掘深度 Maximum telescopic excavation depth (mm)	4000/5200	**轮胎 Tyre**	
挖掘卸载高度 Excavation unloading height (mm)	4500/5300	规格 Specification	14-17.5/19.5L-24
最大挖掘半径 Maximum excavation radius(mm)	4800/6000	行车制动 Service braking	气顶油钳盘制动 Air-over-oil caliper disc braking
最大举升高度 Maximum excavation radius(mm)	5200/5950	驻车制动 Parking braking	**气刹 Air brake**
挖斗斗容 Bucket capacity (m^3)	0.3	**油量 Oil quantity**	
最大挖掘力 Maximum excavating force (KN)	36	燃油箱 Fuel tank (L)	100
挖斗最大挖掘半径 Maximum excavation radius of the bucket(mm)	840	液压油箱 Hydraulic oil tank (L)	100
挖机回转角度 Rotation angle of the excavator (°)	190	**其他 Other**	
装载参数 Loading parameters		驱动型式 Drive form	四轮驱动 Four-wheel drive
最大卸载高度 Maximum unloading height (mm)	2742	变速型式 Transmission type	液力变速 Hydraulic transmission
最大卸载距离 Maximum unloading distance (mm)	1062	操作系统 Operating system	电磁液压先导操控 Electromagnetic hydraulic pilot control
装斗斗容 Loading bucket capacity (m^3)	1		
崛起力 Rising force	72		

HW40-30 BACKHOE LOADER

HW40-30 型挖掘装载机是一种多功能的工程机械设备，具有许多优点和广泛的应用。它是一种结合了挖掘和装载功能的机器，能够在建筑工地、矿山和农田等各种场合发挥重要作用。

The HW40-30 excavator loader is a multifunctional construction machinery equipment with many advantages and wide applications. It is a machine that combines excavation and loading functions and can play an important role in various occasions such as construction sites, mines, and farmland.



技术参数

Machine detailed parameters

HW40-30 技术参数			
整机操作重量 Overall Operating Weight	10500kg	**驱动桥 Axle**	
运输尺寸 Transport Dimension		型号 Model	WZL100DF
长 × 宽 × 高 L*W*H	6420×2530×3120mm	轮边减速型式 Final Reducer	一级轮边减速 Single Stage Final Reducer
轴距 Wheel base	2335mm	额定桥载荷 Rated Bridge Load	13T
整机高度 Overall Height	3120mm	**变矩器 Torque Converter**	
装载斗容 Bucket Capacity	1.2m³	型号 Model	YJ320
掘起力 Breakout Force	47KN	型式 Type	单级、单相三元件 Single-stage Three Elements
装载举升能力 Loading Lifting Capacity	2500KG	冷却方式 Cooling Method	油冷压力循环 Oil-cooling Pressure Circulation
铲斗卸载高度 Bucket Dumping Height	3050mm	**变速箱 Gearbox**	
铲斗卸载距离 Bucket Dumping Distance	870mm	型式 Type	机械操纵液力同步换档 Hydraulic Synchronous Shift Controlled Mechanically
反铲斗容 Backhoe Capacity	0.3m³	型号 Model	ZL15
最大挖掘深度 Max. Digging Depth	3820mm	档位数 Gears	Forward 4, Reverse 4
挖斗回转角 Swing Angle of backhoe	180°	最高车速 Max.Speed	36km/h
最大牵引力 Max. Pulling Force	50KN	轮胎规格 Tyre Model	16.9-28
发动机 Engine		前轮气压 Pressure of Front wheel	0.35 Mpa
品牌 / 型号 Brand/Model	玉柴 Yuchai YC4A105Z-T20	后轮气压 Pressure of Back Wheel	0.35 Mpa
型式 Type	直列、直喷、四冲程 Inline/Direct Injection/Four-stroke	行车制动 Service Brake	气顶油钳盘制动 Air Over Oil Caliper Brake
额定功率 Rated Power	75kw		内置式 Integrated
额定转速 Rated Speed	2200r/min		自调节 Self-regulation
最低燃油率 Min. Fuel Consumption Rate	≤ 230g/km.h		自平衡 Self-balance
最大扭矩 Maximum Torque	≥ 400N.m	驻车 / 紧急制动 Emergency Brake	操纵力实施制动 Operation Power Implementing brake
排量 Displacement	4.8L		手操纵力解除制动 Manual Operation Power Terminating Brake
转向系统 Steering System		**液压系统 Hydraulic System**	
转向器型号 Steering Gear Model	BZZ5-250	工作泵排量	63ml/r
转向角 Steering Angle	±35°	工作泵压力	20Mpa
最小转弯半径 Min. turning radius	6950mm	液压油箱容积	130L
系统压力 Pressure of the system	14Mpa	柴油箱容积	130L

资质证书
PRODUCT ADVANTAGES



































售后服务
AFTER-SALES SERVICE

24小时热线

24-hour hotline

您有任何需要，只需要拨打 24 小时售后服务热线 400-9975-666。

If you have any needs, just call the 24-hour after-sales service hotline 400-9975-666.

15分钟回复

15 minutes to reply

接到售后需求后，售后服务工程师将主动和您取得联系，向您了解设备情况和服务需求，通过电话，微信视频等远程指导处理问题。

After receiving after-sales needs, the after-sales service engineer will take the initiative to contact you to understand the equipment situation and service needs, and provide remote guidance to solve problems through telephone, WeChat video, etc.



24小时出发

24 hours departure

若电话指导无法处理好故障，服务工程师在 24 小时内携带维修工具出发，前往设备所在现场，进行现场维修服务。

If the telephone guidance cannot handle the fault well, the service engineer will set off with the maintenance tools within 24 hours, go to the site where the equipment is located, and perform on-site maintenance services.

重大情况处理

Handling of major situations

重大和特别情况，服务体系将启动快速反应机制、专家支持机制和配件绿色通道。

In major and special circumstances, the service system will start a rapid response mechanism, an expert support mechanism and a green channel for accessories.video.

电话回访

Telephone return visit

现场服务完工后，公司总部呼叫中心将有服务专员对每次服务进行电话回访，跟踪完成情况和服务质量，听取客户意见和建议并反馈到各职能部门进行落实和改善，以便为客户提供更优质的售后服务。

After the on-site service is completed, the call center of the company's headquarters will have a service specialist to conduct a return call for each service, track the completion status and service quality, listen to customer opinions and suggestions, and feed back to each functional department for implementation and improvement, so as to provide customers with better quality.